



# Miragrid<sup>®</sup> 24XT

Miragrid<sup>®</sup> 24XT geogrid is composed of high molecular weight, high tenacity polyester multifilament yarns woven in tension and finished with a PVC coating. Miragrid<sup>®</sup> 24XT geogrid is inert to biological degradation and resistant to naturally encountered chemicals, alkalis, and acids.

Miragrid<sup>®</sup> 24XT geogrid is used as soil reinforcement in MSE structures such as segmental retaining walls, precast modular block walls, wire faced walls, geosynthetic wrapped faced walls and steepened slopes. Miragrid<sup>®</sup> 24XT is also used in MSE stabilized platforms for voids bridging, embankments on soft soils, landfill veneer stability, reducing differential settlement and for foundation seismic stability.

TenCate Geosynthetics Americas is accredited by Geosynthetic Accreditation Institute – Laboratory Accreditation Program (GAI-LAP).

MECHANICAL PROPERTIES	TEST METHOD	UNIT	MINIMUM AVERAGE ROLL VALUE
			MD
Tensile Strength @ Ultimate	ASTM D6637 (Method B)	lbs/ft (kN/m)	27415 (400.0)
Tensile Strength @ 5% strain	ASTM D6637 (Method B)	lbs/ft (kN/m)	7000 (102.1)
Mass/Unit Area <sup>1</sup>	(ASTM D5261)	oz/yd² (g/m²)	32.6 (1119)
			MINIMUM ROLL VALUE
Creep Rupture Strength <sup>2</sup>	ASTM D5262/D6992	lbs/ft (kN/m)	19038 (277.8)
Long Term Design Strength <sup>3</sup>		lbs/ft (kN/m)	16483 (240.5)
PHYSICAL PROPERTIES		UNIT	ROLL CHARACTERISTIC
Roll Dimensions <sup>4</sup> (width x length)		ft (m)	12 x 200 (3.6 x 61)
			12 x 1000 (3.6 x 305)
Roll Area		yd² (m²)	267 (220)
			1333 (1114)
Estimated Roll Weight		lbs (kg)	595 (270)
			2840 (1287)
Label Roll Color			WHITE

<sup>&</sup>lt;sup>1</sup> Minimum Average Roll Values (MARV) shown above are based on QC Testing per a defined lot not to exceed 12 months. Testing

Disclaimer: TenCate assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Mirafi\* is a registered trademark of Nicolon Corporation. Copyright © 2021 Nicolon Corporation. All Rights Reserved FGS000094 ETQR23







Frequency follows ASTM D4354, Table 1.

<sup>&</sup>lt;sup>2</sup> 75-year design life based on NTPEP Report REGEO-2016-01-070.

<sup>&</sup>lt;sup>3</sup> Long Term Design Strength for sand, silt, clay.  $RF_{CR} = 1.44$ ;  $RF_{ID} = 1.05$ ;  $RF_{D} = 1.1$ 

<sup>(</sup>Installation damage reduction factor for other soils available upon request).

<sup>&</sup>lt;sup>4</sup> Special order roll lengths are available upon request









# **LOCATIONS & CONTACT INFO**

## **ASP ENTERPRISES**

aspent.com

salesasp@aspent.com

St. Louis, MO Omaha. NE 636.343.4357

Kansas City, MO 816.554.1191

402.861.8579

Wichita, KS 316 393 1554

# **BOWMAN CONSTRUCTION SUPPLY**

bowmanconstructionsupply.com

salesbcs@bowmanconstructionsupply.com salesquick@quicksupplyco.com

Denver. CO Loveland, CO 303.696.8960 970.535.0863

> Colorado Springs, CO 719.257.7840

**OUICK SUPPLY CO.** 

quicksupplyco.com

Des Moines, IA 515.289.1271

#### **CASCADE GEOSYNTHETICS**

cascadegeos.com

salescascade@cascadegeos.com

Portland, OR 971.339.1020

Salt Lake City, UT 435.276.0820

# **SOLUTIONS WE SUPPLY**

## **GEOSYNTHETICS**

Filter Fabrics

Stabilization Fabrics

# Geogrids

- Road Grids
- Wall Grids
- Slope Stabilization

#### **Specialty Fabrics**

# **Composite Geomembranes**

• GCLs, PVC, HDPE, LLDPE, EPDM, Granular Bentonite

### **SEDIMENT CONTROL**

#### **Inlet Protection**

· Grated Inlet, Curb Inlet, Area Inlet Protection

#### **Ditch Checks**

- · Triangle Silt Dike
- GeoRidge

## **Perimeter Protection**

- · High and Low-Porosity Silt Fence, Straw Wattles, Silt Socks
- Safety Fence

## Flocculants & Water Treatment

Polymer-Based & Natural Flocculants

# Sediment Basin Skimmers **Dewatering Bags**

#### **Trackout Control**

- FODS
- Rumble Grates

# **Turbidity Curtains**

## **EROSION CONTROL**

## **Basic Hydraulically Applied Mulches**

- Wood
- Paper
- Blends
- Straw

# **High-Performance Hydraulically Applied Products**

- FGM
- Additives & Tackifiers

## **Temporary Erosion Control Blankets**

- Coir & Jute Mat/Nettings
- Short-Term ECBs
- Extended-Term ECBs

# **Permanent Erosion Control Blankets**

- Turf Reinforcement Mats
- HP-TRMs
- Anchor Reinforced Vegetation System

#### Structural BMPs

- Transition Mats
- Geoweb Cellular Confinement
- Composite Vegetated Armor System
- Flex MSE Vegetated Wall System
- Articulated Concrete Block
- Gabions
- · Grout-Filled Geotextile Mats

### Vegetation Establishment

- · Native Seed & Turf Seed
- Fertilizers
- · Organic Soil Additives
- Stratavault Soil Cells

## STORMWATER MANAGEMENT

## Water Quality

- Inlet Filter Boxes
- Pre-Treatment Chamber
- Nutrient Separating Baffle Boxes
- · High-Flow Biofiltration Media
- · Hydrodynamic Separators
- Stratavault

## Water Ouantity

- · Modular Underground Storage Systems
- Chamber Detention Systems

# Drainage

- HDPE Swale Liner
- Pipe & Fittings
- Drainage Composites
- Strip Drain

# **Inlet Structures**

- PVC
- Drain Basis. In-Line Drains
- Landscape

# Permeable Pavers

- · Permeable Articulating Concrete Block
- Grass Pavers
- Gravel Pavers
- Concrete Pavers

## **SPECIALTY**

Natural & Synthetic Coir Fiber Logs Vegetated Reinforced Soil Slopes Soil Anchors **Root Barrier System** AquaBlok Muscle Wall

We are full line distributors of construction materials for all project types. Contact us for assistance with a project. From specification and development to installation and completion, we're here to help with all of your site solution needs.